

# Kidde ECS Fire Suppression System Component Description


Cylinder and Valve Assemblies 10 lb. (4.5 kg) to 70 lb.  
(31.7 kg) Capacity, Vertical Mount Only

P/N: 90-10000X0-001



## FEATURES

- For Use with UL Listed, ULC Listed and FM Approved Systems
- RoHS Complaint
- See Kidde USCG Approved Manual for USCG Approval



## ORDERING INFORMATION

Part Number	Cylinder Size	Dimensions (inches)		
		A	B	C
90-100010-001	10 lb.	7.07	13.34	17.30
90-100020-001	20 lb.	7.07	21.01	24.97
90-100040-001	40 lb.	9.00	22.80	26.76
90-100070-001	70 lb.	9.00	34.87	38.83

## MATERIALS

- Valve Body: Brass
- Cylinder: Steel, Painted Red

## COMPATIBILITY

Series	For Use With
Kidde ECS HFC-227ea	X

## Notes:

1. The safety cap must be installed on the valve outlet at all times, except when the cylinders are connected to the system piping, or being filled. The safety cap must not be removed from its chain.
2. See K-90-2070 for additional information.
3. Cylinders are vertical mount only.

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly. If you need more information on this product, or if you have a particular problem or question, contact KIDDE-FENWAL, Inc.

Kidde is a registered trademark of Kidde-Fenwal Inc. All other trademarks are the property of their respective owners.