Kidde Engineered Fire Suppression System

Designed for use with 3M™ Novec™ 1230 Fire Protection Fluid

Effective: June 2015

K-45-2120 Rev AE

Flexible Discharge Hose Data Sheet

FEATURES

- ***UL Listed, ULC Listed, and FM Approved for use with Novec 1230 Systems***



TECHNICAL DATA

- Minimum Bursting Pressure: 2000 PSI
- Working Pressure: 500 PSI
- Proof Pressure: 1000 PSI

MATERIALS

- Hose: Reinforced Rubber Hose
- Fitting: Cadmium-plated Steel

ORDERING INFORMATION

Part Number	Male NPT	Dimension A	Min. Bend Radius
283898	1-1/2 in.	24 in.	10-1/2 in.
283899	2 in.	31 in.	13-1/2 in.
283900	2-1/2 in.	48 in.	22-1/2 in.

Kidde is a registered trademark of Kidde-Fenwal, Inc.
3M and Novec are trademarks of 3M.
All other trademarks are property of their respective owners.

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly.If you need more information on this product, or if you have a particular problem or question, contact KIDDE-FENWAL, Inc.

©2015 Kidde-Fenwal, Inc.

Kidde Fire Systems
400 Main Street
Ashland, MA 01721
Ph: 508.881.2000
Fax: 508.881.8920
www.kiddefiresystems.com