Kidde Engineered Fire Suppression System

Designed for use with 3M™ Novec™ 1230 Fire Protection Fluid

Effective: June 15

K-45-5100 Rev AC

3/8 in. Check Valve

FEATURES

- ***UL Listed, ULC Listed, and FM Approved for use with Novec 1230 Systems***

P/N: 261193



TECHNICAL DATA

- Working Pressure: 0 to 5000 PSI (0 to 345 bar)
- Proof Pressure: 10000 PSI (690 bar)
- Cracking Pressure: 2 to 4 PSI (0.14 to 0.28 bar)
- Operating Temperature: -40°F to 250°F (-40°C to 121°C)

MATERIALS

- Body: Brass
- Seal: BUNA-N

Kidde is a registered trademark of Kidde-Fenwal, Inc.
3M and Novec are trademarks of 3M.
All other trademarks are property of their respective owners.

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly.If you need more information on this product, or if you have a particular problem or question, contact KIDDE-FENWAL, Inc.

©2015 Kidde-Fenwal, Inc.

Kidde Fire Systems
400 Main Street
Ashland, MA 01721
Ph: 508.881.2000
Fax: 508.881.8920
www.kiddefiresystems.com