Kidde Engineered Fire Suppression System

Designed for use with 3M™ Novec™ 1230 Fire Protection Fluid

Effective: June 2014

Cable Housing for Cable Operated Control Heads

K-45-6030 Rev AC

FEATURES

- ***UL Listed, ULC Listed, and FM Approved for use with Novec 1230 Systems***

P/Ns: 260702, 260951, AND 263602



Part Number	Cylinders Used With	Cylinder Centers	Dimension A
260702	125, 200 lb. (56.7, 90.7 kg)	15 in. (381 mm)	10.6 in. (270 mm)
260951	350 lb. (158.7 kg)	18 in. (457 mm)	13.6 in. (346 mm)
263602	600 lb. (272.1 kg)	24 in. (610 mm)	19.6 in. (498 mm)

MATERIALS

- Brass, 0.625 (16 mm) x O.D. x 0.049 in. (1.28 mm) Wall

Kidde is a registered trademark of Kidde-Fenwal, Inc.
3M and Novec are trademarks of 3M.
All other trademarks are property of their respective owners.

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly.If you need more information on this product, or if you have a particular problem or question, contact KIDDE-FENWAL, Inc.

©2015 Kidde-Fenwal, Inc.

Kidde Fire Systems
400 Main Street
Ashland, MA 01721
Ph: 508.881.2000
Fax: 508.881.8920
www.kiddefiresystems.com